



Specifications & Operating Parameters

Pore Sizes

40 series

1A, 0.35, 1, 5, 10, 20, 50, 100 and 150 microns

Nominal Lengths

Surface Area

10 001100	00,0 (2110 0111)	10 09 10
90 series	19 1/2" (49.5 cm)	90 sq ft
170 series	30 3/4" (78.1 cm)	170 sq ft

9 5/8" (24.5 cm)

Outside Diameter

7 3/4" (19.68 cm)

Materials of Construction

Filter Media:	Polypropylene
Inner Core:	Polypropylene
End caps:	Polypropylene
Gaskets:	EPR Standard. Contact factory for other
	available options

- Available in 0.35 to 150 micron ratings
- Large diameter, single cartridge construction makes installations and change outs simple and quick with minimal handling
- High media surface area for maximizing service life and optimizing filter performance and value
- Rugged construction designed for residential, commercial and industrial use, and made in the USA
- Compatible with wide range of potable water and aqueous industrial applications
- Available in three sizes for flow rates up to 150 GPM
- 20 micron and above cartridges may be washed and reused
- Center tube, end caps, and media are all polypropylene
- Thermally bonded construction provides additional strength

Applications

RO Prefilters		
Process Water		
Swimming Pools		
Plating Solutions		

Food & Beverage Bottled Water Spas Water & Wastewater

Operating Temperature Range: 40°F (4.4°C) – 140°F (60°C)


Recommended Change-out Differential Pressure 20-25 psid (1.4 – 1.7 bar)

Maximum Flow Rates Per Cartridge – GPM (LPM)

Sorios

Series				
40	90	170		
20 (75.7)	40 (151.4)	80 (302.8)		
25 (94.6)	50 (189.3)	100 (378.5)		
30 (113.6)	60 (227.2)	120 (454.2)		
50 (189.3)	100 (378.5)	150 (567.8)		
50 (189.3)	100 (378.5)	150 (567.8)		
50 (189.3)	100 (378.5)	150 (567.8)		
50 (189.3)	100 (378.5)	150 (567.8)		
50 (189.3)	100 (378.5)	150 (567.8)		
50 (189.3)	100 (378.5)	150 (567.8)		
	20 (75.7) 25 (94.6) 30 (113.6) 50 (189.3) 50 (189.3) 50 (189.3) 50 (189.3) 50 (189.3) 50 (189.3)	20 (75.7) 40 (151.4) 25 (94.6) 50 (189.3) 30 (113.6) 60 (227.2) 50 (189.3) 100 (378.5) 50 (189.3) 100 (378.5) 50 (189.3) 100 (378.5) 50 (189.3) 100 (378.5) 50 (189.3) 100 (378.5) 50 (189.3) 100 (378.5) 50 (189.3) 100 (378.5) 50 (189.3) 100 (378.5)		

Flow vs. Pressure Drop



Ordering Guide (Example: SJC-170-5)

SJC -	- 170 -	- 5
MODEL	SERIES	MICRONS
SJC	40 90 170	1A 0.35 1 5 10 20 50 100 150

Filter Housings

Shelco manufactures a full line of filter housings. From our rugged single cartridge housings to our heavy duty multi-cartridge housings and bag filter housings, Shelco is the perfect choice for your filtration solutions.



Shelco Filters 100 Bradley Street Middletown, CT 06457 USA

Tel: 800-543-5843 / Fax: 860-854-6120 / E-mail: info@shelco.com

MicroSentryTM, MicroVantageTM, Shelco Filters[®] and the Shelco logo are registered trademarks of the Tinny Corporation. Shelco Filters is a division of the Tinny Corporation.